

Atrust All-in-One- A200Z



- 1 Power Button**
Use this button for turning on and off.
- 2 LAN Port**
It connects to a host server through a LAN switch.
- 3 USB 2.0 Port**
It connects to USB device.
- 4 USB 2.0 Port**
It connects to USB device.
- 5 DVI-I Port**
It connects to a monitor.
- 6 DC IN**
It connects to an AC adaptor.
- 7 Microphone Port**
It connects to a microphone.
- 8 Headphone Port**
It connects to a headphone or a speaker system.
- 9 USB 2.0 Port x 2**
It connects to USB devices.
- 10 USB 2.0 Port x 2**
It connects to USB devices.



Atrust All-in-One - A200Z

System	
Processor	Teradici® TERA2321
Memory	
System memory	512MB
Display	
LCD Type/Resolution	23.6" LED Backlight / 1920 x 1080 pixels
I/O Interfaces	
I/O ports	1 x DVI-I port, 6 x USB 2.0, 1 x Headphone port, 1 x Microphone port, 1 x RJ-45, 1 x DC IN
Networking	
LAN	10/100/1000Mb
Dimensions / Weight	
Dimensions	(W) 569.6 x (D) 183.5 x (H) 412.3 mm (with stand)
Weight	4.85kg (approximate)
Environment	
Cooling	Fanless
Operating noise	No noise
Operating temperature	5°C ~ 35°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 90% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adaptor	19V, 65W, 3.42A
Software	
Protocol	VMware® Horizon View™

© 2017 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.