

# Atrust

## Atrust 14" Mobile Thin Client mt182W



**1 Web Camera**

Built-in web camera.

**2 Power Button**

Press to turn on the client.

**3 Keyboard**

Built-in keyboard for control and input.

**4 Fingerprint Reader**

Built-in fingerprint reader.

**5 Speakers**

Built-in Speaker for audio output.

**6 Touchpad**

Built-in pointing device for control and input.

**7 DC IN**

Connects to an AC adapter.

**8 HDMI**

Connects to external display.

**9 USB 3.1 Gen 1 Type-C**

Connects to a USB device.

**10 Audio Combo**

Connects to a set of headphones system.

**11 Kensington Lock Slot**

Connects a Kensington cable to secure the mobile thin client.

**12 USB 3.1 Gen 1 Type-C**

Connects to a USB device.

**13 USB 3.1 Gen 1 Type-A**

Connects to a USB device.

**14 USB 3.1 Gen 1 Type-A**

Connects to a USB device.

### Atrust mt182W Features

▶ **Low total cost of ownership**

Additional computing access is as simple as adding more thin client devices. The total cost of ownership is then drastically reduced.

▶ **Simple click and play**

Connects this device to the host server with a Remote Session connection. Just click the shortcut for a Remote Desktop session, you can immediately start a session and enjoy the computing resources.

▶ **Rich remote user experience**

Support Citrix® HDX/ICA™, Microsoft® RDP™ with RemoteFX™ and VMware® Horizon View™, this device can provide a rich and efficient computing experience.

▶ **Easy management and maintenance**

Since all computing tasks are mainly performed on a server, all hardware and software issues are significantly reduced on the client side. All user management, software installations, system management, and upgrades are done on a single server.



## Atrust mt182W Mobile Thin Client

System	
Processor	Intel® Braswell Quad Core X5-E8000 1.04G (Burst to 2.0G)
Memory	
System memory	4GB
Flash memory	32GB
Display	
LCD Type/Resolution	14" / 1920 x 1080 FHD
I/O Interfaces	
I/O ports	1 x HDMI, 2 x USB 3.1 Gen 1 Type-A, 2 x USB 3.1 Gen 1 Type-C, 1 x Audio Combo, 1 x DC IN, 1 x Fingerprint Reader, 1 x Web Camera, 2 x 2W Internal Speaker, 1 x Internal Microphone * USB3.1 Gen1 Type-C port did not support display function
Networking	
Ethernet	USB 3.1 to Gigabit Ethernet Adapter
Wireless	IEEE 802.11ac/a/b/g/n, BlueTooth v5.1
Dimensions / Weight	
Dimensions	(W) 322 x (D) 222 x (H) 15.95 mm
Weight	1.2 kg (approximate)
Environment	
Operating temperature	5°C ~ 35°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
Power Adapter	
AC Adapter	19V, 65W, 3.42A
Software	
Operating system	Windows® 10 IoT Enterprise 2016 LTSC Windows® 10 IoT Enterprise 2019 LTSC
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™

© 2023 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit [www.atrustcorp.com](http://www.atrustcorp.com).