


Atrust s101F Mini Server

1 2 3 4	Atrust	
5		

- 1 Power Button Press to turn on the server.
- 2 Power LED Indicates the status of power.3 HDD LED
- Indicates the status of HDD (Hard Disk Drive)
- 4 Alert/UID LED Indicates system abnormalities & UID (Unit Identification) status.
- 5 USB 2.0 Port x 2 Connects to the USB device.

- 6 USB 3.0 Port x 2 Connects to the USB device.
- **VGA Port** Connects to a monitor.
- 8 LAN Port(shared Management) Connects to a switch.
- 9 LAN Port Connects to a switch.
- 10 UID LED UID (Unit Identification) status.



6

7

8 9

10

11

12

ĩ-

2 Kensington Lock Slot Connects a Kensington cable to secure the device.

Atrust s101F supports a wide range of operating systems and is designed for:

- Efficient energy consumption
- Low IT administration cost
- Rapid and easy installation
- High reliability and durability
- Comprehensive support for various remote desktop and application delivery services

Atrust s101F

System	s101F
Processor	Intel [®] Xeon [®] E-2278GE Processor 3.3GHz Intel [®] Xeon [®] E-2278G Processor 3.4GHz (option)
Chipset	Intel® C246
Memory Module	128GB
Graphics	VGA:1920x1080
Storage	2 x 2.5" 1TB SATA HDD or 1 x 2.5" 1TB and 2 x 960GB M.2 SSD
I/O Ports	Front : 2 x USB 2.0, 1 x Power LED, 1 x Alert/UID LED, 1 x HDD LED(Status/Access) Rear : 2 x USB 3.0, 1 x 1GbE LAN port, 1 x 1GbE LAN port for shared NIC management (BMC), 1 x VGA port, 1 x UID LED
Networking	1 x Gigabit Ethernet 1 x Gigabit Ethernet (shared Management port)
Form Factor	Mini Server
Dimension	(W) 70 x (H) 196 x (D) 188 mm
Weight	Approximate 2.4 kg
Operating Temperature	5°C ~ 35°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity (Rh)	20% ~ 80% (non-condensing)
Non-operating Humidite (Rh)	5% ~ 95%
Operating Voltage Range	100 ~ 240 VAC
Rated Line Frequency	50 ~ 60Hz
Maximum Output Power	AC adaptor 180W
Operating System	Microsoft® Windows Server® 2019 Microsoft® Windows Server® 2016 Microsoft® Windows® Hyper-V Server 2019 Microsoft® Windows® Hyper-V Server 2016 Microsoft® Windows® Hyper-V Server 2012 R2 Red Hat® Enterprise Linux® 8.1 SUSE® Linux Enterprise Server 15 SP1
Management	Remote Management Interface

© 2022 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Red Hat, Red Hat Enterprise Linux are trademarks or registered trademarks of Red Hat, Inc.. SUSE is registered trademark of SUSE LLC. To learn more, visit www.atrustcorp.com.

