## **Atrust**

## Thin Client Atrust t10L





**7** DC IN **1** Microphone Port Connects to a microphone. Connects to an AC adaptor. 8 LAN Port **2** Headphone Port Connects to a headphone or a speaker system. Connects to a host server through a LAN switch. 9 USB 2.0 Port x 2 Connects to a USB device. 3 USB 3.0 Port Connects to a USB device. 4 USB 2.0 Port 10 DVI-I Port Connects to a USB device. Connects to a monitor. 5 Power LED 11 RS-232 Port Connects to a serial port device. Indicates the status of power. 6 Power Button 12 Antenna (Manufacturing option) Press to turn on/off the client. Connects to a wireless network. Atrust **Atrust t10L Features** Durable and quiet design Low power consumption Simplified management Lower total cost of ownership (TCO) Slim and robust design Supported Protocols t10L supports the following protocols: Citrix<sup>®</sup> ICA/HDX<sup>™</sup>, Microsoft<sup>®</sup> RDP<sup>™</sup> with RemoteFX<sup>™</sup>, VMware<sup>®</sup> Horizon View<sup>™</sup>

## Atrust t10L

System	t10L
Processor	Intel <sup>®</sup> Bay Trail Dual Core 1.58GHz
Memory	
System memory	2GB
Flash memory	4GB
Graphics	
Maximum resolution	Up to 1920 x 1200
I/O Interfaces	
I/O ports	Front: 1 x USB 3.0, 1 x USB 2.0, 1 x Microphone port, 1 x Headphone port, Rear: 1 x DVI-I, 2 x USB 2.0, 1 x RS-232 port, 1 x RJ-45, 1 x DC IN
Networking	
Ethernet	10/100/1000Mb
Dimensions / Weight	
Dimensions	(W) 155 x (D) 109.6 x (H) 37 mm
Weight	810g (approximate, with WiFi antenna)
Environment	
Cooling	Fanless
Operating noise	No noise
Operating temperature	-20°C ~ 55°C
Non-operating temperature	-40°C ~ 80°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
Rated output current (max)	3A
Output voltage	+12V DC
Power consumption : Suspend / Idle / Active	0.45W / 4.67W / 5.71W
Software	
Operating system	Atrust OS
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix <sup>®</sup> ICA/HDX <sup>™</sup> , Microsoft <sup>®</sup> RDP <sup>™</sup> with RemoteFX <sup>™</sup> , VMware <sup>®</sup> Horizon View <sup>™</sup> (PCoIP/RDP/Blast)
Regulatory	CB, NRTL, FCC, CE, VCCI
Option	WiFi antenna

© 2017 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.

