





Thin Client Atrust t185W

- 1 Power LED**
Indicates the status of power.
- 2 Power Button**
Press to turn on/off the client.
- 3 Audio Combo**
Headphone / Microphone Combo.
- 4 USB-A Port (USB 2.0)**
Connects to a USB device.
- 5 USB-C Port (USB 3.2 Gen 1)**
Connects to a USB device.
- 6 Kensington Security Slot**
Connects a Kensington cable to secure the thin client.
- 7 Displayport x 2**
Connects to a monitor.
- 8 USB-A Port (USB 3.2 Gen 1) x 2**
Connects to a USB device.
- 9 USB-A Port (USB 2.0) x 2**
Connects to a USB device.
- 10 LAN Port**
Connects to a host server through a LAN switch.
- 11 DC IN**
Connects to an AC adapter.



Atrust t185W

- ▶ Dual display support
- ▶ Low power consumption
- ▶ Durable and quiet design
- ▶ Lower total cost of ownership (TCO)
- ▶ Simplified management

Atrust t185W

System	
Processor	Intel® Elkhart Lake J6412 Quad Core 2.0 GHz (up to 2.6 GHz)
Memory	
System memory	8 GB (Manufacturing option : 16 GB / 32 GB)
Storage	64 GB (Manufacturing option : 128 GB / 256 GB)
Graphics	
Maximum resolution	Up to 4096 x 2160 @ 60Hz
I/O Interfaces	
I/O ports	Front : 1 x USB-A Port (USB 2.0), 1 x USB-C Port (USB 3.2 Gen 1), 1 x Audio Combo Rear : 2 x DisplayPort, 2 x USB-A Port (USB 2.0), 2 x USB-A Port (USB 3.2 Gen 1) 1 x LAN Port, 1 x DC IN, 1 x Kensington Security Slot * USB-C Port (USB 3.2 Gen 1) did not support display function
Networking	
Ethernet	10 M / 100 M / 1 G
WiFi	802.11 a / b / g / n / ac (Manufacturing option)
Dimensions / Weight	
Dimensions	(W) 39.5 x (D) 103 x (H) 143 mm
Weight	425 g (approximate)
Environment	
Cooling	Fanless
Operating noise	No noise
Operating temperature	0°C ~ 35°C
Non-operating temperature	-30°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
Power Supply	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adapter	12V, 3A
Software	
Operating system	Windows® 10 IoT Enterprise LTSC 2021 Windows® 11 IoT Enterprise LTSC 2024
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA / HDX™, Microsoft® RDP™ with RemoteFX™ Microsoft® Remote Desktop for Azure Virtual Desktop and Windows 365 Omnissa Horizon®
Manufacturing options	WiFi & Bluetooth Combo * The dimensions would become (W) 39.5 x (D) 103 x (H) 151 mm if goes with WiFi.

Copyright © 2025 Atrust Computer Corp. Other trademarks may be trademarks of their respective owners.
The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein.
To learn more, visit www.Atrustcorp.com.