



Atrust

Quad-Display

Thin Client t226W

Atrust t226W is a Windows Embedded OS based thin client computer. Developed by Atrust, the ACS (Atrust Client Setup) software is also built in to help effective management of t226W. With the support of Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™ and VMware® Horizon View™, t226W can be used to create virtual and session-based desktop experiences from many remote desktop capable operating systems. t226W offers a rich computing experience where applications look, feel, and behave as local devices, including high-definition multimedia content.



1 Power Button

Press to turn on/off the client.

2 Power LED

Lights blue when powered on.

3 Microphone Port

Connects to a microphone.

4 Headphone Port

Connects to a set of headphones or speaker system.

5 USB 2.0 Port x 2

Connects to a USB device.

6 USB 3.2 Gen 1 x 2

Connects to a USB device.

7 USB 3.2 Gen 2 Type C

Connects to a USB device.

8 Kensington Lock Slot

Connects a Kensington cable to secure the thin client.

9 USB 2.0 Port x 2

Connects to a USB device.

10 USB 3.2 Gen 1 x 2

Connects to a USB device.

11 DisplayPort x 4

Connects to a monitor.

12 LAN Port

Connects to a local area network.

13 DC IN

Connects to an AC adaptor.

Atrust t226W Features

- ▶ Quad display support
- ▶ Simplified management
- ▶ Slim and robust design
- ▶ Low power consumption
- ▶ Lower total cost of ownership (TCO)
- ▶ Supported Protocols
t226W supports the following protocols:
Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™

Atrust t226W

System	
Processor	Intel® Tiger Lake i3-1115G4, 3.0 GHz (Max Turbo 4.10 GHz)
Memory	
System memory	4 GB (Manufacturing option : 8 GB / 16 GB / 32 GB / 64 GB)
Flash memory	64 GB (Manufacturing option : 128 GB / 256 GB / 512 GB)
Graphics	
Maximum resolutions	DisplayPort : 4096 x 2160@60Hz
I/O Interfaces	
I/O ports	Front : 2 x USB 2.0, 2 x USB 3.2 Gen 1 Type-A, 1 x USB 3.2 Gen 2 Type-C 1 x Microphone Port, 1 x Headphone Port Rear : 4 x DisplayPort, 2 x USB 2.0, 2 x USB 3.2 Gen 1 Type-A, 1 x RJ-45 1 x DC IN, 1 x Kensington lock slot
Networking	
Ethernet	10 M / 100 M / 1 G / 2.5 G
Dimensions / Weight	
Dimensions	(W) 45.6 x (D) 189 x (H) 204 mm
Weight	1.2 Kg with stand (approximate)
Environment	
Cooling	Fan
Operating noise	No noise
Operating temperature	0°C ~ 35°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adapter	19V, 90W, 4.74A / 19V, 65W, 3.42A
Software	
Operating system	Windows®10 IoT Enterprise 2019 LTSC
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA / HDX™ Microsoft® RDP™ with RemoteFX™ VMware® Horizon View™ (PCoIP / RDP / Blast)
Manufacturing options	WiFi : IEEE 802.11 a / b / g / n / ac Smart Card Reader 2 x COM Port 2nd LAN (2.5 Gbps) TPM (Trusted Platform Module)

© 2023 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.Atrustcorp.com.