





Thin Client Atrust t185L

- 1 Power LED**
Indicates the status of power.
- 2 Power Button**
Press to turn on / off the client.
- 3 Audio Combo**
Headphone / Microphone Combo.
- 4 USB 2.0 Port x 1**
Connects to a USB device.
- 5 USB 3.2 Gen 1 Type C**
Connects to a USB device.
- 6 Kensington Lock Slot**
Connects a Kensington cable to secure the thin client.
- 7 DisplayPort x 2**
Connects to a monitor.
- 8 USB 3.2 Gen 1 x 2**
Connects to a USB device.
- 9 USB 2.0 Port x 2**
Connects to a USB device.
- 10 LAN Port**
Connects to a host server through a LAN switch.
- 11 DC IN**
Connects to an AC adapter.



Atrust t185L

- ▼ Dual display support
- ▼ Durable and quiet design
- ▼ Simplified management
- ▼ Low power consumption
- ▼ Lower total cost of ownership (TCO)

Atrust t185L Thin Client

System	t185L
Processor	Intel® Elkhart Lake J6412 Quad Core 2.0GHz (up to 2.6GHz)
Memory	
System memory	4GB (Manufacturing option : 8GB / 16GB)
Storage	16GB (Manufacturing option : 64GB)
Graphics	
Maximum resolution	Up to 4096 x 2160 @ 60Hz
I/O Interfaces	
I/O ports	Front : 1 x USB 2.0, 1 x USB 3.2 Gen 1 Type C, 1 x Audio Combo, Rear : 2 x DisplayPort, 2 x USB 2.0, 2 x USB 3.2 Gen 1, 1 x RJ-45, 1 x DC IN, 1 x Kensington lock slot * USB3.2 Gen1 Type-C port did not support display function
Networking	
Ethernet	10 / 100 / 1000 Mbps
WiFi	802.11 a/b/g/n/ac (Manufacturing option)
Dimensions / Weight	
Dimensions	(W) 39.5 x (D) 103 x (H) 143 mm
Weight	425g (approximate)
Environment	
Cooling	Fanless
Operating noise	No noise
Operating temperature	0°C ~ 35°C
Non-operating temperature	-30°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
Rated output current (max)	3A
Output voltage	+12V DC
Software	
Operating system	Atrust OS
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA / HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™ (PCoIP / RDP / Blast)
Manufacturing options	WiFi & Bluetooth Combo * The dimensions would become (W) 39.5 x (D) 103 x (H) 151 mm if goes with WiFi.

© 2024 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.