



Thin Client

Atrust w200L

High-Performance Linux-Based Thin Client

The Atrust w200L is a powerful, all-new Linux-based thin client engineered to meet the demands of modern cloud computing and virtual desktop infrastructures (VDI). Driven by the robust AMD Ryzen™ Embedded R2314 processor, the w200L delivers a seamless, high-definition computing experience that bridges the gap between remote sessions and local performance.

- 1 Power LED**
Indicates the status of power.
- 2 Power Button**
Press to turn on/off the client.
- 3 Audio Combo**
Headphone / Microphone Combo.
- 4 USB-C Port (USB 3.2 Gen 1)**
Connects to a USB device.
- 5 USB-A Port (USB 2.0) x 2**
Connects to a USB device.
- 6 Kensington Security Slot**
Connects to a Kensington security lock.
- 7 DisplayPort x 2**
Connects to a monitor.
- 8 USB-A Port (USB 3.2 Gen 1) x 2**
Connects to a USB device.
- 9 USB-A Port (USB 2.0) x 2**
Connects to a USB device.
- 10 LAN Port**
Connects to a LAN switch.
- 11 DC IN**
Connects to an AC adaptor.



Atrust w200L

- ▶ **Dual-Monitor Ready**
High-resolution support for enhanced workflow.
- ▶ **Built to Last**
Durable, compact design for maximum reliability.
- ▶ **Effortless IT Control**
Simplified management via built-in ACS software.
- ▶ **Energy Efficient**
Low power consumption for a greener workspace.
- ▶ **Maximum ROI**
Lower Total Cost of Ownership (TCO) through centralized management.

Atrust w200L

Processor	AMD Ryzen™ Embedded R2314 (Manufacturing option : R2312)
Memory	
System memory	4 GB (Manufacturing option : 8 GB / 16 GB)
Storage	64 GB
Graphics	
Maximum resolution	Up to 4096 x 2160 @ 60Hz
I/O Interfaces	
I/O ports	Front : 2 x USB-A Port (USB 2.0), 1 x USB-C Port (USB 3.2 Gen 1), 1 x Audio Combo Rear : 2 x DisplayPort, 2 x USB-A Port (USB 3.2 Gen 1), 2 x USB-A Port (USB 2.0) 1 x LAN Port, 1 x DC IN, 1 x Kensington Security Slot * USB-C Port (USB 3.2 Gen 1) did not support display function
Networking	
Ethernet	10 M / 100 M / 1 G
WiFi	802.11 a / b / g / n / ac / ax (Manufacturing option)
Dimensions / Weight	
Dimensions	(W) 39.5 x (D) 103 x (H) 143 mm
Weight	450 g (approximate)
Environment	
Operating temperature	0°C ~ 40°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
Power Supply	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adaptor	19V, 65W, 3.42A
Software	
Operating System	Atrust OS
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA / HDX™, Microsoft® RDP™ with RemoteFX™, Omnisca Horizon®
Security	
TPM	fTPM 2.0 (Manufacturing option : dTPM 2.0)
Manufacturing options	WiFi & Bluetooth Combo * The dimensions would become (W) 39.5 x (D) 103 x (H) 151 mm if goes with WiFi.

Copyright © 2026 Atrust Computer Corp. Other trademarks may be trademarks of their respective owners.
The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein.
To learn more, visit www.Atrustcorp.com.